Q.HOME⁺ ESS HYB-G1/AC

MODULAR ENERGY STORAGE SOLUTION FOR NORTH AMERICA*

BATTERY CHARGER /

BI-DIRECTIONAL

INVERTER

LITHIUM-ION

10 YEAR PRODUCT

WARRANTY

BATTERY





SCALABLE SOLUTION FOR OPTIMIZED CONSUMPTION

Scalable storage capacity from 4.5 kWh up to 18.9 kWh to suit all consumption cases.



Modular design for easy and fast installation, ability to operate with existing PV inverter and microinverter, lithium-ion battery, and battery charger.

REMOTE MONITORING

Easy maintenance due to its early error detection function, web and mobile monitoring, and a reliable service network.



SAFETY AND RELIABILITY

Premium quality lithium-ion.



DURABILITY

High durability with 10 year product warranty and 90% depth of discharge (DoD).



100% BACKUP POWER FUNCTION

Thanks to the integrated backup power function, even in the event of power failure 100% of the rated inverter output will support critical loads.

* This specification is applicable for an AC-coupled configuration

THE IDEAL SOLUTION FOR:



╺┣╋┟

\$

Rooftop arrays on residential buildings



TECHNICAL SPECIFICATIONS

SENERAL PRODUCT INFORMATION			Q.HOME*	ESS HYB-G1				
		6.0 kW	7.0 kW	7.6 kW	8.6kW			
Dimensions inverter / storage (L × W × D)	[in]	36 × 22 × 10.9 (913 × 560 × 276 mm) / 18.3 × 7.6 × 23.1 in (464 × 193 × 588 m						
Neight inverter / storage (4.5kWh) / storage (6.3kWh)	[lbs]	1	L30 (58.9 kg)/124.8 (56.6kg)/148.4 (67.5k	g)			
Operating temperature inverter / storage	[°F]	32~113 (0~45°C)/32~113 (0~45°C)						
Relative humidity	[%]	0-100						
Enclosure rating		Туре 4Х						
Nounting			Wall mounted					
Max. operating height without power loss	[m]	2000						
Cooling method		Natural						
Noise emissions	[dB]	≤35						
AC over voltage category			I,	/IV				
Front panel display		LCD						
Communications		RS485/LAN/CAN 2.0/WiFi/4G (optional)						
Remote monitoring		Web, mobile						
Software update		Local USB/Remote Web						
Energy management system		Integrated						
GRID DATA (AC)								
Nax. output power / Rated output power	[kVA]	6.6/6	7.7/7	8.36/7.6	9.46/8.6			
lominal voltage / Range	[V]	120/240 split phase (105.5/211~132/264)						
lominal grid frequency / Range	[Hz]	60/59.3~60.5						
Iominal current	[A]	25	29	32	36			
Naximum AC output current protection	[A]	28	32	35	41			
Power factor		>99 (adj. ±0.8)						
Fotal harmonic distorsion	[%]	≤3						
BACKUP POWER OUTPUT (AC)								
Nax. output power / Rated output power	[kW]	6.6/6	7.7/7	8.36/7.6	9.46/8.6			
Nax. output current / Rated output current	[A]	28/25	32/29	35/32	41/36			
Rated voltage	[V]		120/240) split phase				
Rated frequency	[Hz]	60						
Switchover time to backup power		<200ms						
Support by PV during backup power operation		YES						
EFFICIENCY								
Max. battery-AC	[%]	96.46						
CEC efficiency (PV-Battery) / (Battery-AC)	[%]	95.50/95.63						
BATTERY DATA (DC)								
Battery technology		Lithium-ion (NMC)						
Battery usable capacity per module	[kWh]	4.5/6.3						
Scalability		Up to three battery modules						
Max. battery usable capacity	[kWh]	13.5/18.9						
Rated power / Max. power (with three battery modules)	[kW]	7.5/8.3						
Rated battery voltage / Battery voltage range (per module)	[Vdc]	100.8/85~118						
Battery management mystem voltage range	[Vdc]	84 - 432						
Rated discharging current	[A]		25					
Depth of discharge (DoD)	[%]	90						
COUNTRY AVAILABILITY / CERTIFICATES AND WARRANTY	[,0]							
nverter certificates		17 <u>/</u> 1 17/1 C	A 111 9540 IEEE 1547	IEEE 15471				
		UL 1741, UL 1741.SA, UL 9540, IEEE 1547, IEEE 1547.1, CSA – C 22.2N.107.1-01, UL 1998, UL 1699B, FCC part 15 Class B						
		CSA – C 22.2N 107	.1-01. UL 1998. UL 169	J9B. FCC part 15 Class	UL 1642, UL 1973, CE, RCM, TUV (IEC 62619), UN 3480, Class 9, UN 38.3			
Battery certificates								

NOTE: Installation instructions must be followed. See the installation and operating manual or contact our technical service department for further information on approved installation and use of this product.

Hanwha Q CELLS America Inc.

400 Spectrum Center Drive, Suite 1400, Irvine, CA 92618, USA | TEL +1 949 748 59 96 | EMAIL inquiry@us.q-cells.com | WEB www.q-cells.us

